


LARGE CAPACITY AIR CONDITIONERS **2012 / 2013**





Panasonic Air Conditioning Designed To Care For Your Projects

With more than 30 years of experience, exporting to more than 120 countries around the world, Panasonic is unquestionably one of the leaders in the air conditioning sector. The company is also a world leader in innovation as it has filed more than 91,539 patents to improve its customers' lives. Moreover, Panasonic is determined to remain at the forefront of its market. In all, the company has produced more than 200 million compressors and its products, particularly residential air conditioners, now hold the No. 1 market share in Japan and other major countries in Asia. You can be assured of the extremely high quality of Panasonic's air conditioners.

This wish to excel has made Panasonic the international leader in air conditioning solutions. The company's industrial capacity and firm commitment to the environment has enabled it to open new avenues of research and to develop innovative technologies which enhance its customers' way of life.

Panasonic offers a range of turnkey air conditioning solutions for homes and medium-sized buildings such as offices and restaurants. These offer maximum effectiveness, comply with the strictest environmental standards and meet the most avant-garde construction requirements of our time.

At Panasonic we know what a great responsibility it is to install cooling and heating systems. Because offering you the best solutions in cooling and heating matters.

EVERY BUILDING MATTERS

Panasonic

INVERTER

CONTENTS

| | |
|---------------------|---------|
| Introduction | 02 - 03 |
| Product Range | 04 - 05 |
| Outdoor Units | 06 - 11 |
| Indoor Units | |
| Ducted type | 12 - 15 |
| 4-Way Cassette type | 16 - 19 |
| Controllers | 20 - 35 |

Panasonic provides ideal solutions
for large-capacity air conditioning needs



Indoor
Units

CAPACITY (kW)

6.0kW

Ducted

S-60PE1R5

Page 12-15



4-Way Cassette

* Panel is a separate accessory (CZ-KPU2)

S-60PU1R5

Page 16-19



Outdoor
Units

CAPACITY (kW)

6.0kW

Page 6-11

U-60PE1R5



EVERY BUILDING MATTERS



7.1kW

10.0kW

12.5kW

14.0kW

S-71PE1R5

S-100PE1R5

S-125PE1R5

S-140PE1R5



S-71PU1R5

S-100PU1R5

S-125PU1R5

S-140PU1R5



7.1kW

10.0kW

12.5kW

14.0kW

U-71PE1R5

U-100PE1R5
U-100PE1R8*

U-125PE1R5
U-125PE1R8*

U-140PE1R5
U-140PE1R8*



(*3-phase)

Outdoor Units

DC Inverter allows both comfort and energy savings



- Complies with all necessary Safety Approvals to ensure quality and safety
- Top-class EER:4.20 / COP:4.31 (Cassette type:10.0kW)
- Compiled Demand Response (DRED Compatible)
- Cooling operation is possible when outdoor temperature is as high as 46°C
- DC inverter technology combined with R410A for excellent efficiency
- Maximum piping length:75m (Total piping length:75m)
- Cooling operation is possible when outdoor temperature is as low as -15°C
- Heating operation is possible when outdoor temperature is as low as -20°C
- One ampere starting current
- Auto restart from outdoor unit





Product Quality and Safety

All Panasonic air conditioners undergo strict quality and safety tests before sale. This rigorous process includes obtaining all necessary Safety Approvals to ensure that all air conditioners we sell are not only built to the highest market standards, but are also completely safe.

Energy-saving concept

The use of energy-saving designs for the structure of fans, fan motors, compressors and heat exchangers results in high COP values which rank amongst the highest in the industry. In addition, use of highly efficient R410A refrigerant reduces CO2 emission and lowers operating costs.



① Compact & High-Efficiency Compressor

A large-capacity inverter compressor has been adopted. The inverter compressor is superior in performance with improved partial-load capacity.

② Printed Circuit Board (S-LINK)

The number of PCB were reduced from 3 into 2 pieces making maintenance work easier.

③ DC fan motor

Checking load and outside temperature, the DC motor is controlled for optimum air volume.

④ New Large Diagonal (520mm) Air Flow Fan

The newly designed fan has been developed to inhibit air turbulence and to increase efficiency. As the fan diameter has been increased to 520mm, the air volume has been increased whilst maintaining a low sound level.

⑤ High-Efficiency Heat Exchanger


The heat exchanger and the size of the copper tubes heat exchanger have been redesigned to increase efficiency.

Outdoor Units


Improved Energy Savings

The operation efficiency has been improved using highly efficient R410A refrigerant, a new DC inverter compressor, a new DC motor and a newly designed heat exchanger.

Cooling (Ducted)




Heating (Ducted)




Wide Operating Range

- Cooling operation is possible when outdoor temperature is as low as -15°C
 - Cooling operation is possible when outdoor temperature is as high as 46°C
 - Heating operation is possible when outdoor temperature is as low as -20°C
- The remote controller temperature setting offers a range from 16°C to 30°C



Increased Piping Length for Greater Design Flexibility

Adaptable to various building types and sizes
 Max. piping length : 75m (10.0kW, 12.5kW, 14.0kW),
 50m (6.0kW, 7.1kW)




Max. piping length: 75m (10.0kW, 12.5kW, 14.0kW)
50m (6.0kW, 7.1kW)

Demand Response Compliant

Panasonic air conditioners are equipped with Demand Response Capability which complies to both AS 4755 and AS 3823. Panasonic continues to design and develop products that are tailored to local needs and requirements. This ensures that Panasonic products that you are installing today are compliant with the demand response standards that are likely to be implemented shortly (estimate: 2012).

The Equipment Energy Efficiency (E3) program has been supporting the development of Demand Response Enabling Device (DRED) standards for air-conditioners which should comply with AS 4755. DRED functionality is not compulsory today, however, this capability will be required for all installations in the very near future.



Demand control terminal is available to control 0-50-75-100% of capacities.

Compact and Lightweight

The weight is only 98kg (10.0kW, 12.5kW, 14.0kW)
Hence it is easy to carry, easy to install.



Compact & Flexible-design

The slim and lightweight design can be installed in various places.




Quiet Mode

Quiet Mode reduces outdoor unit operating sound by 5dB. External input signal is also available.



Outdoor Units

Dimensions (6.0kW - 7.1kW)




- 1 Mounting hole (4-R6.5), anchor bolt : M10
- 2 Refrigerant piping (liquid pipe), flared connection (ø9.52)
- 3 Refrigerant piping (gas pipe), flared connection (ø15.88)
- 4 Electrical wiring port (ø13)
- 5 Electrical wiring port (ø22)
- 6 Electrical wiring port (ø27)
- 7 Electrical wiring port (ø35)

Indoor Units

Ducted

Hidden in the ceiling to provide an ideal match for luxury homes and light commercial buildings





S-60PE1R5
S-71PE1R5
S-100PE1R5



S-125PE1R5
S-140PE1R5


Compact Body Size

Hidden in the ceiling, ideal when interior decor is an important consideration such as in homes with many rooms and light commercial buildings.



System Example


An inspection port (450 mm x 450 mm or more) is required at the control-box side of the indoor unit body.






Cold Drafts Reduced During Heating

- Accurate temperature measurement by E1/E2 sensor to reduce cold drafts when in heating mode.




Indoor Units Ducted

Dimensions




Dimensions: mm

| model | A | B | C | D |
|--------------------------|-----|------|-----|-------|
| S-60PE1R5 | 130 | 33.1 | 290 | 118 |
| S-71PE1R5 S-100PE1R5 | 195 | 35.7 | 360 | 50 |
| S-125PE1R5 S-140PE1R5 | 260 | 38.2 | 430 | 121.5 |



| Capacity | | | 6.0KW | 7.1KW | 10.0KW | |
|--|-------------------|----------|--|--|--|--|
| Model Name | Indoor Unit | | S-60PE1R5 | S-71PE1R5 | S-100PE1R5 | S-100PE1R5 |
| | Outdoor Unit | | U-60PE1R5 | U-71PE1R5 | U-100PE1R5 | U-100PE1R8 |
| Power source | | Phase/Hz | 1 Phase/ 50Hz | 1 Phase/ 50Hz | 1 Phase/ 50Hz | 3 Phase/ 50Hz |
| | | V | 230V 240V | 230V 240V | 230V 240V | 400V 415V |
| Cooling capacity Heating capacity | | kW | 6.0 (2.5 - 7.1) 7.0 (2.0 - 8.5) | 7.1 (2.5 - 8.2) 8.0 (2.0 - 9.0) | 10.0 (3.3 - 12.5) 11.2 (4.1 - 14.0) | 10.0 (3.3 - 12.5) 11.2 (4.1 - 14.0) |
| | | BTU/h | 20,500 (8,500 - 24,200) 23,900 (6,800 - 29,000) | 24,200 (8,500 - 28,000) 27,300 (6,800 - 30,700) | 34,100 (11,300 - 42,700) 38,200 (14,000 - 47,800) | 34,100 (11,300 - 42,700) 38,200 (14,000 - 47,800) |
| EER : COP | | W/W | 3.24 : 3.41 | 3.23 : 3.48 | 3.36 : 3.52 | 3.36 : 3.52 |
| Total power input | Cooling : Heating | kW | 1.85 : 2.05 | 2.20 : 2.30 | 2.98 : 3.18 | 2.98 : 3.18 |
| Indoor Unit | | | | | | |
| Current | Cooling : Heating | A | 0.85 : 0.85 0.86 : 0.86 | 1.24 : 1.24 1.25 : 1.25 | 1.72 : 1.72 1.74 : 1.74 | 1.72 : 1.72 1.74 : 1.74 |
| Dimensions | H x W x D | mm | 290x1,100 (+100)x700 | 360x1,100 (+100)x700 | 360x1,100 (+100)x700 | 360x1,100 (+100)x700 |
| Net weight | | kg | 35 | 42 | 44 | 44 |
| Air volume | Cooling : Heating | L/s | 366 : 366 | 500 : 500 | 666 : 666 | 666 : 666 |
| External static pressure | | Pa | 70 (Max.100) | 100 (Max.150) | 100 (Max.150) | 100 (Max.150) |
| Sound pressure level (H/M/L) | Cooling : Heating | dB(A) | 43 / 41 / 40 : 43 / 41 / 40 | 45 / 44 / 43 : 45 / 43 / 44 | 48 / 46 / 44 : 48 / 46 / 44 | 48 / 46 / 44 : 48 / 46 / 44 |
| Sound power level (H/M/L) | Cooling : Heating | dB(A) | 60 / 58 / 57 : 60 / 58 / 57 | 62 / 61 / 60 : 62 / 61 / 60 | 70 / 68 / 66 : 70 / 68 / 66 | 70 / 68 / 66 : 70 / 68 / 66 |
| Number of fan speeds | | | 3 | 3 | 3 | 3 |
| Drain pipe size | | mm | VP-25 | VP-25 | VP-25 | VP-25 |
| Outdoor Unit | | | | | | |
| Current | Cooling : Heating | A | 7.85 : 8.80 7.65 : 8.60 | 9.10 : 9.30 8.80 : 9.00 | 11.8 : 12.7 11.40 : 12.3 | 3.95 : 4.25 3.80 : 4.10 |
| Dimensions | H x W x D | mm | 996 x 940 x 340 | 995 x 940 x 340 | 1,416 x 940 x 340 | 1,416 x 940 x 340 |
| Net weight | | kg | 68 | 69 | 98 | 98 |
| Air volume | Cooling : Heating | L/s | 1,000 : 1,000 | 1,000 : 1,000 | 1,833 : 1,583 | 1,833 : 1,583 |
| Sound pressure level (Silent mode) | Cooling : Heating | dB(A) | 48 (46) : 50 (48) | 48 (46) : 50 (48) | 52 (50) : 52 (50) | 52 (50) : 52 (50) |
| Sound power level (Silent mode) | Cooling : Heating | dB(A) | 65 (63) : 67 (65) | 65 (63) : 67 (65) | 69 (67) : 69 (67) | 69 (67) : 69 (67) |
| Piping connections | Liquid/Gas | m | Ø9.52 / Ø15.88 | Ø9.52 / Ø15.88 | Ø9.52 / Ø15.88 | Ø9.52 / Ø15.88 |
| Pipe length | min. - max. | m | 5 - 50 | 5 - 50 | 5 - 75 | 5 - 75 |
| Elevation difference (OU located lower, OU located higher) | | m | 15, 30 | 15, 30 | 15, 30 | 15, 30 |
| Maximum chargeless length | | m | 30 | 30 | 30 | 30 |
| Refrigerant at shipping, Additional gas amount | | g | R410A 2,000, 50 (g/m) | R410A 2,350, 50 (g/m) | R410A 3,400, 50 (g/m) | R410A 3,400, 50 (g/m) |
| Operation ranges | Cooling : Heating | °C | -15 to 46 : -20 to 24 | -15 to 46 : -20 to 24 | -15 to 46 : -20 to 24 | -15 to 46 : -20 to 24 |



Optional Controller



Timer remote controller
CZ-RTC2



Wireless remote controller
CZ-RWSC2



Simplified remote controller
CZ-RE2C2



Backlit remote controller
CZ-RELC2

| 12.5KW | | 14.0KW | |
|--|--|--|--|
| S-125PE1R5 | S-125PE1R5 | S-140PE1R5 | S-140PE1R5 |
| U-125PE1R5 | U-125PE1R8 | U-140PE1R5 | U-140PE1R8 |
| 1 Phase/ 50Hz | 3 Phase/ 50Hz | 1 Phase/ 50Hz | 3 Phase/ 50Hz |
| 230V 240V | 400V 415V | 230V 240V | 400V 415V |
| 12.5 (3.3 - 14.0) 14.0 (4.1 - 16.0) | 12.5 (3.3 - 14.0) 14.0 (4.1 - 16.0) | 14.0 (3.3 - 15.5) 16.0 (4.1 - 18.0) | 14.0 (3.3 - 15.5) 16.0 (4.1 - 18.0) |
| 42,700 (11,300 - 47,800) 47,800 (14,000 - 54,600) | 42,700 (11,300 - 47,800) 47,800 (14,000 - 54,600) | 47,800 (11,300 - 52,900) 54,600 (14,000 - 61,400) | 47,800 (11,300 - 52,900) 54,600 (14,000 - 61,400) |
| 3.21 : 3.37 | 3.21 : 3.37 | 3.15 : 3.52 | 3.15 : 3.52 |
| 3.90 : 4.16 | 3.90 : 4.16 | 4.45 : 4.55 | 4.45 : 4.55 |
| 1.82 : 1.82 1.84 : 1.84 | 1.82 : 1.82 1.84 : 1.84 | 2.62 : 2.62 2.70 : 2.70 | 2.62 : 2.62 2.70 : 2.70 |
| 430x1,100 (+100)x700 | 430x1,100 (+100)x700 | 430x1,100 (+100)x700 | 430x1,100 (+100)x700 |
| 48 | 48 | 53 | 53 |
| 833 : 833 | 833 : 833 | 1,000 : 1,000 | 1,000 : 1,000 |
| 100 (Max.150) | 100 (Max.150) | 100 (Max.150) | 100 (Max.150) |
| 49 / 47 / 45 : 49 / 47 / 45 | 49 / 47 / 45 : 49 / 47 / 45 | 51 / 49 / 47 : 51 / 49 / 43 | 51 / 49 / 47 : 51 / 49 / 43 |
| 71 / 69 / 67 : 71 / 69 / 67 | 71 / 69 / 67 : 71 / 69 / 67 | 73 / 71 / 69 : 73 / 71 / 67 | 73 / 71 / 69 : 73 / 71 / 67 |
| 3 | 3 | 3 | 3 |
| VP-25 | VP-25 | VP-25 | VP-25 |
| 16.0 : 17.2 15.4 : 16.6 | 5.30 : 5.70 5.10 : 5.50 | 17.8 : 18.1 17.2 : 17.5 | 5.80 : 5.95 5.55 : 5.70 |
| 1,416 x 940 x 340 | 1,416 x 940 x 340 | 1,416 x 940 x 340 | 1,416 x 940 x 340 |
| 98 | 98 | 98 | 98 |
| 2,166 : 1,833 | 2,166 : 1,833 | 2,250 : 2,000 | 2,250 : 2,000 |
| 53 (51) : 53 (51) | 53 (51) : 53 (51) | 54 (52) : 55 (53) | 54 (52) : 55 (53) |
| 70 (68) : 70 (68) | 70 (68) : 70 (68) | 71 (69) : 71 (69) | 71 (69) : 71 (69) |
| Ø9.52 / Ø15.88 | Ø9.52 / Ø15.88 | Ø9.52 / Ø15.88 | Ø9.52 / Ø15.88 |
| 5 - 75 | 5 - 75 | 5 - 75 | 5 - 75 |
| 15, 30 | 15, 30 | 15, 30 | 15, 30 |
| 30 | 30 | 30 | 30 |
| R410A 3,400, 50 (g/m) | R410A 3,400, 50 (g/m) | R410A 3,400, 50 (g/m) | R410A 3,400, 50 (g/m) |
| -15 to 46 : -20 to 24 | -15 to 46 : -20 to 24 | -15 to 46 : -20 to 24 | -15 to 46 : -20 to 24 |

Indoor Units

4-WAY Cassette

Provides a neat fit in the ceiling to match modern decor, uniform cooling throughout the room, plus easy installation



Technical focus

- Compact design
- Reduced sound levels (from previous models)
- DC fan motor for increased efficiency
- Powerful drain pump gives 850 mm lift
- Lightweight design
- Fresh air knockout
- Branch duct connection
- Optional air-intake plenum CZ-FDU2


Wide & Comfortable Airflow

Comfort/Quiet

A proprietary design features wide-angle discharge outlets and flaps that are larger in the middle, featuring a shape that was selected based on both physics and testing of actual prototype units. Air coming out of the center of the discharge outlets travels farther. From the sides of each outlet, where the openings are larger, airflow spreads out to reach the corners of the room. Air is discharged across a wide area from the four sides of the unit. The curves on the room temperature distribution graph expand gently out through 360° in a circle centred on the indoor unit.


Ample airflow: 36 m³/min

Industry's highest in the 14.0kW class.



Temperature distribution by thermograph (cooling operation)

Simulation conditions:
P140 4-way ceiling-mounted cassette type in cooling mode
/ Floor area of 225 m²
/ Ceiling height of 3 m



AIR INTAKE CHAMBER



PANEL



CZ-KPU2

1 Air intake box CZ-BCU2 for main unit.

2 Air intake box CZ-ATU2 for Air intake plenum.

* When using Air intake box (CZ-ATU2), Air intake plenum (CZ-FDU2) required.



High-Ceiling Installation (Up to 5 m for 10.0kW+ models)

The units can be installed in rooms with high ceilings where they provide ample floor-level heating in the winter. (See ceiling height guidelines below.)

| High Ceiling (Factory settings) | | | |
|---------------------------------|------------|--|---------------------|
| New model | | | |
| | Capacity | | Capacity |
| | 60PU, 71PU | | 100PU, 125PU, 140PU |

| | | | |
|-------------|--|---|---|
| 100PU-140PU | | | |
| | 4-way discharge high ceiling settings 2 | 3-way discharge with the optional air-blocking materials | 2-way discharge with the optional air-blocking materials |

Ceiling height guidelines

| Indoor unit | *1 settings | 4-way discharge | | | 3-way discharge (optional air-blocking materials) | 2-way discharge *2(optional air-blocking materials) |
|---------------------|-------------|--------------------|------------------------|------------------------|--|--|
| | | Factory settings 1 | High ceiling setting 1 | High ceiling setting 2 | | |
| 60PU-71PU | | 3.0 | 3.3 | 3.6 | 3.8 | 4.2 |
| 100PU, 125PU, 140PU | | 3.6 | 3.9 | 4.5 | 4.7 | 5.0 |

*1 When using the unit in a configuration other than the factory settings, it is necessary to make settings on site to increase airflow.

*2 Use air-blocking materials (CZ-CFU2) to completely block two discharge outlets for 2-way airflow.

Indoor Unit

4-way Cassette

Easy Maintenance and Cleaning

The flaps can be removed easily for washing with water.



It is easy to remove the washable flaps by hand.



The suction grill allows 90-degree turns.

Low-Profile 33.5 mm Panel

The square panel integrates seamlessly with the ceiling. Discharge outlets close when the unit is stopped.




One of the industry's thinnest panels

Protrusion of **33.5 mm**


Lighter and Slimmer, Easier Installation

A lightweight unit at 24kg, the unit is also very slim with a height of only 256mm, making installation possible even in narrow ceilings. * For 6.0kW, 7.1kW



A Drain Height of Approx. 850mm from the Ceiling Surface

The drain height can be increased by approximately 350mm over the conventional value by using a high-lift drain pump, and long horizontal piping is possible.



| Capacity | | | 6.0kW | 7.1kW | 10.0kW |
|--|-------------------|-------|--|--|--|
| Model Name | Indoor Unit | | S-60PU1R5 | S-71PU1R5 | S-100PU1R5 |
| | Outdoor Unit | | U-60PE1R5 | U-71PE1R5 | U-100PE1R5 |
| | PANEL | | CZ-KPU2 | CZ-KPU2 | CZ-KPU2 |
| Power source | Phase/Hz | | 1 phase, 50Hz | 1 phase, 50Hz | 1 phase, 50Hz |
| | V | | 230V 240V | 230V 240V | 230V 240V |
| Cooling capacity Heating capacity | kW | | 6.0 (2.5 - 8.0) 7.0 (2.0 - 8.5) | 7.1 (2.5 - 8.2) 8.0 (2.0 - 9.0) | 10.0 (3.3 - 12.5) 11.2 (4.1 - 14.0) |
| | | | 20,500 (8,500 - 27,300) 23,900 (6,800 - 29,000) | 24,200 (8,500 - 28,000) 27,300 (6,800 - 30,700) | 34,100 (11,300 - 42,700) 38,200 (14,000 - 47,800) |
| | BTU/h | | | | |
| EER : COP | Cooling : Heating | W/W | 4.05 : 3.87 | 3.94 : 4.00 | 4.20 : 4.31 |
| Total power input | Cooling : Heating | kW | 1.48 : 1.81 | 1.80 : 2.00 | 2.38 : 2.60 |
| Indoor Unit | | | | | |
| Current | Cooling : Heating | A | 0.31 : 0.30 0.30 : 0.29 | 0.33 : 0.32 0.32 : 0.31 | 0.71 : 0.65 0.71 : 0.64 |
| Dimensions H x W x D | Indoor | mm | 256 x 840 x 840 | 256 x 840 x 840 | 319 x 840 x 840 |
| | Panel | mm | 33.5 x 950 x 950 | 33.5 x 950 x 950 | 33.5 x 950 x 950 |
| Net weight | Indoor | kg | 24 | 24 | 27 |
| | Panel | kg | 4 | 4 | 4 |
| Air volume | Cooling : Heating | L/s | 350 : 350 | 366 : 366 | 550 : 550 |
| Sound pressure level (H/M/L) | Cooling : Heating | dB(A) | 36 / 31 / 28 : 36 / 31 / 28 | 37 / 31 / 28 : 37 / 31 / 28 | 44 / 38 / 32 : 44 / 38 / 32 |
| Sound power level (H/M/L) | Cooling : Heating | dB(A) | 53 / 48 / 45 : 53 / 48 / 45 | 54 / 48 / 45 : 54 / 48 / 45 | 62 / 55 / 49 : 62 / 55 / 49 |
| Number of fan speeds | | | 3 | 3 | 3 |
| Drain pipe size | | mm | VP-25 | VP-25 | VP-25 |
| Outdoor Unit | | | | | |
| Current | Cooling : Heating | A | 6.90 : 8.20 6.70 : 7.95 | 8.10 : 9.00 7.90 : 8.70 | 10.3 : 11.4 9.90 : 11.0 |
| Dimensions H x W x D | | mm | 996 x 940 x 340 | 996 x 940 x 340 | 1,416 x 940 x 340 |
| | | kg | 68 | 69 | 98 |
| Air volume | Cooling : Heating | L/s | 1,000 : 1,000 | 1,000 : 1,000 | 1,833 : 1,583 |
| Sound pressure level (Silent mode) | Cooling : Heating | dB(A) | 48 (46) : 50 (48) | 48 (46) : 50 (48) | 52 (50) : 52 (50) |
| Sound power level (Silent mode) | Cooling : Heating | dB(A) | 65 (63) : 67 (65) | 65 (63) : 67 (65) | 69 (67) : 69 (67) |
| Piping connections | | m | Ø9.52 / Ø15.88 | Ø9.52 / Ø15.88 | Ø9.52 / Ø15.88 |
| Pipe length min. - max. | | m | 5 - 50 | 5 - 50 | 5 - 75 |
| Elevation difference (OU located lower, OU located higher) | | m | 15, 30 | 15, 30 | 15, 30 |
| Maximum chargeless length | | m | 30 | 30 | 30 |
| Refrigerant at shipping, Additional gas amount | | g | R410A 2,000, 50 (g/m) | R410A 2,350, 50 (g/m) | R410A 3,400, 50 (g/m) |
| Operation ranges | Cooling : Heating | °C | -15 - 46 : -20 - 24 | -15 - 46 : -20 - 24 | -15 - 46 : -20 - 24 |

- 1 Air intake grill
- 2 Air discharge outlet
- 3 Refrigerant piping (liquid pipes) : $\varnothing 9.52$ (flared)
- 4 Refrigerant piping (gas pipes) : $\varnothing 15.88$ (flared)
- 5 Drain outlet VP25(outlet $\varnothing 32$)
- 6 Power supply port
- 7 Discharge duct ($\varnothing 150$)
- 8 Suspension bolt hole (4-12x30 slot)
- 9 Fresh air intake duct connection port ($\varnothing 100$)*1



* Adjust the suspension bolt length so that the gap from the lower ceiling surface becomes 30 mm or more (18 mm or more from the lower surface of the body) as shown in the figure. When the suspension bolt length is long, it hits the ceiling panel and installation is not possible.

| 12.5kW | | 14.0kW | |
|-----------------------------|-----------------------------|-----------------------------|-----------------------------|
| S-125PU1R5 | S-125PU1R5 | S-140PU1R5 | S-140PU1R5 |
| U-125PE1R5 | U-125PE1R8 | U-140PE1R5 | U-140PE1R8 |
| CZ-KPU2 | CZ-KPU2 | CZ-KPU2 | CZ-KPU2 |
| 1 phase, 50Hz | 3 phase, 50Hz | 1 phase, 50Hz | 3 phase, 50Hz |
| 230V 240V | 400V 415V | 230V 240V | 400V 415V |
| 12.5 (3.3 - 14.0) | 12.5 (3.3 - 14.0) | 14.0 (3.3 - 15.5) | 14.0 (3.3 - 15.5) |
| 14.0 (4.1 - 16.0) | 14.0 (4.1 - 16.0) | 16.0 (4.1 - 18.0) | 16.0 (4.1 - 18.0) |
| 42,700 (11,300 - 47,800) | 42,700 (11,300 - 47,800) | 47,800 (11,300 - 52,900) | 47,800 (11,300 - 52,900) |
| 47,800 (14,000 - 54,600) | 47,800 (14,000 - 54,600) | 54,600 (14,000 - 61,400) | 54,600 (14,000 - 61,400) |
| 3.60 : 4.00 | 3.60 : 4.00 | 3.25 : 3.70 | 3.25 : 3.70 |
| 3.47 : 3.50 | 3.47 : 3.50 | 4.31 : 4.33 | 4.31 : 4.33 |
| | | | |
| 0.76 : 0.73 0.73 : 0.73 | 0.76 : 0.73 0.73 : 0.73 | 0.89 : 0.80 0.87 : 0.79 | 0.89 : 0.80 0.87 : 0.79 |
| 319 × 840 × 840 | 319 × 840 × 840 | 319 × 840 × 840 | 319 × 840 × 840 |
| 33.5 × 950 × 950 | 33.5 × 950 × 950 | 33.5 × 950 × 950 | 33.5 × 950 × 950 |
| 27 | 27 | 27 | 27 |
| 4 | 4 | 4 | 4 |
| 583 : 583 | 583 : 583 | 600 : 600 | 600 : 600 |
| 45 / 39 / 33 : 45 / 39 / 33 | 45 / 39 / 33 : 45 / 39 / 33 | 46 / 40 / 34 : 46 / 40 / 34 | 46 / 40 / 34 : 46 / 40 / 34 |
| 63 / 56 / 50 : 63 / 56 / 50 | 63 / 56 / 50 : 63 / 56 / 50 | 64 / 57 / 51 : 64 / 57 / 51 | 64 / 57 / 51 : 64 / 57 / 51 |
| 3 | 3 | 3 | 3 |
| VP-25 | VP-25 | VP-25 | VP-25 |
| | | | |
| 15.3 : 15.4 14.8 : 14.9 | 5.15 : 5.20 5.00 : 5.05 | 19.0 : 19.2 18.4 : 18.6 | 6.45 : 6.50 6.20 : 6.25 |
| 1,416 × 940 × 340 | 1,416 × 940 × 340 | 1,416 × 940 × 340 | 1,416 × 940 × 340 |
| 98 | 98 | 98 | 98 |
| 2,166 : 1,833 | 2,166 : 1,833 | 2,250 : 2,000 | 2,250 : 2,000 |
| 53 (51) : 53 (51) | 53 (51) : 53 (51) | 54 (52) : 55 (53) | 54 (52) : 55 (53) |
| 70 (68) : 70 (68) | 70 (68) : 70 (68) | 71 (69) : 71 (69) | 71 (69) : 71 (69) |
| 09.52 / 015.88 | 09.52 / 015.88 | 09.52 / 015.88 | 09.52 / 015.88 |
| 5 - 75 | 5 - 75 | 5 - 75 | 5 - 75 |
| 15, 30 | 15, 30 | 15, 30 | 15, 30 |
| 30 | 30 | 30 | 30 |
| R410A 3,400, 50 (g/m) | R410A 3,400, 50 (g/m) | R410A 3,400, 50 (g/m) | R410A 3,400, 50 (g/m) |
| -15 - 46 : -20 - 24 | -15 - 46 : -20 - 24 | -15 - 46 : -20 - 24 | -15 - 46 : -20 - 24 |

Optional Controller



Timer remote controller
CZ-RTC2



Wireless remote controller
CZ-RWSU2



Wireless remote controller
CZ-RWSC2








Simplified remote controller
CZ-RE2C2

Backlit remote controller
CZ-BELC2

Controllers

A wide variety of control options to meet the requirements of different applications

| OPERATION SYSTEM | INDIVIDUAL CONTROL SYSTEMS | | | | TIMER OPERATION |
|--|---|---|---|---|---|
| Requirements | Normal operation | Operation from anywhere in the room | Quick and easy operation | | Daily and weekly program |
| External appearance |  |  |  |  |  |
| Type, model name | Timer Remote Controller (Wired) | Wireless Remote Controller | Simplified Remote Controller | Backlit remote controller | Schedule Timer |
| | CZ-RTC2 | CZ-RWSU2 CZ-RWSC2 | CZ-RE2C2 | CZ-RELC2 | CZ-ESWC2 |
| Built-in Thermostat | ● | ● | ● | | — |
| Number of indoor units which can be controlled | 1 group, 8 units | 1 group, 8 units | 1 group, 8 units | | 64 groups, max. 64 units |
| Use limitations | · Up to 2 controllers can be connected per group. | · Up to 2 controllers can be connected per group. | · Up to 2 controllers can be connected per group. | — | · Required power supply from the system controller · When there is no system controller, connection is possible to the T10 terminal of an indoor unit. |
| Function ON/OFF | ● | ● | ● | | — |
| Mode setting | ● | ● | ● | | — |
| Fan speed setting | ● | ● | ● | | — |
| Temperature setting | ● | ● | ● | | — |
| Air flow direction | ● | ● | ● | | — |
| Permit/Prohibit switching | — | — | — | | — |
| Weekly program | ● | — | — | | ● |

1. Setting is not possible when a remote control unit is present. (Use the remote controller for setting.)
All specifications subject to change without notice.










Backlit remote controller [CZ-RELC2]



Dimensions
H 120 x W 70 x D 16 mm

Backlit remote controller with simple and friendly operation


- LCD backlight display
- ON/OFF, operation mode switching, temperature setting, airflow velocity switching, airflow direction setting, alarm display and remote controller self diagnosis can be performed
- Built-in temp sensor
- Batch group control for up to 8 indoor units

| CENTRALISED CONTROL SYSTEMS | | | | | |
|--|--|---|--|---|--|
| Operation with various function from centre station | Only ON/OFF operation from centre station | Simplified load distribution ratio (LDR) for each tenant | BMS System PC Base | Connection with 3rd Party Controller | |
| | | Touch screen panel | | | |
|  |  |  | P-AIMS Basic Software  CZ-CSWKC2 | Seri-Para I/O unit for outdoor unit  | |
| System Controller | ON/OFF Controller | Intelligent Controller | Optional software | Interface adaptor | |
| CZ-64ESMC2 | CZ-ANC2 | CZ-256ESMC2 (CZ-CFUNC2) |  CZ-CSWAC2 for Load distribution CZ-CSWWC2 for Web application CZ-CSWGC2 for Object layout display CZ-CSWBC2 for BAC net software interface *PC required (field supply) | CZ-CAPC2 Seri-Para I/O unit for each indoor unit  CZ-CAPBC2 Communication Adaptor  CZ-CFUNC2 LonWorks Interface  CZ-CLNC2 | |
| — | — | — | | | |
| 64 groups, max. 64 units | 16 groups, max. 64 units | 64 units x 4 systems, max. 256 units | | | |
| · Up to 10 controllers, can be connected to one system. · Main unit/sub unit (1 main unit + 1 sub unit) connection is possible. · Use without remote controller is possible. | · Up to 8 controllers (4 main units + 4 sub units) can be connected to one system. · Use without remote controller is impossible. | · A communication adaptor (CZ-CFUNC2) must be installed for three or more systems. | | | |
| ● | ● | ● | | | |
| ● | — | ● | | | |
| ● | — | ● | | | |
| ● | — | ● | | | |
| ● ¹ | — | ● ¹ | | | |
| ● | ● | ● | | | |
| — | — | ● | | | |

Individual Control Systems

| Control contents | Part name, model No. | Quantity |
|---|--|-------------|
| Standard Control <ul style="list-style-type: none"> Control of the various operations of the indoor unit by wired or wireless remote controller. Cooling or heating mode of the outdoor unit is decided by the first priority of the remote controller. Switching between remote controller sensor and body sensor is possible. | Timer remote controller CZ-RTC2 Simplified remote controller CZ-RE2C2 Backlit remote controller CZ-RELC2 Wireless remote controller CZ-RWSU2 / CZ-RWSC2 | 1 unit each |
| (1) Group control <ul style="list-style-type: none"> Batch remote control on all indoor units. Operation of all indoor cells in the same mode. Up to 8 units can be connected. The sensor is the in-unit sensor, and thermostat ON/OFF setting in regard to the temperature set by the remote controller is possible for each indoor unit. | Timer remote controller CZ-RTC2 Simplified remote controller CZ-RE2C2 Wireless remote controller CZ-RWSU2 / CZ-RWSC2 | 1 unit |
| (2) Main/sub remote control <ul style="list-style-type: none"> Max 2 remote controllers per indoor unit. (Main remote controller can be connected) The button pressed last has priority. Timer setting is possible even with the sub remote controller. | Main or sub Timer remote controller CZ-RTC2 Simplified remote controller CZ-RE2C2 Wireless remote controller CZ-RWSU2 / CZ-RWSC2 | As required |

SYSTEM EXAMPLE



Timer remote controller (CZ-RTC2)



Dimensions
H 120 x W 120 x D 16 mm

Basic remote controller ON/OFF

- Operation mode changeover (Cooling, Heating, Dry, Auto, Fan)
- Temperature setting (Cooling/Dry: 18-30 deg Heating: 16-30 deg).
- Fan speed setting H/ M/ L and Auto
- Air flow direction adjustment

Time Function 24 hours real time clock

- Day of the week indicator

Weekly Programme Function

- A maximum of 6 settings/day and 42 settings/ week can be programmed

Outing Function

- This function can prevent the room temperature from dropping or rising when the occupants are out for a long time

Sleeping Function

- This function controls the room temperature for comfortable sleeping

Built in Temp Sensor

Max. 8 indoor units can be controlled from one remote controller

Remote control by main remote controller and sub controller is possible

Max. 2 remote controllers (main remote controller and sub controller) can be installed for one indoor unit

Wireless remote controller



U1 type
CZ-RWSU2

Remote control by main remote controller and sub controller is possible

- Max. 2 remote controllers (main remote controller and sub controller) can be installed for one indoor unit

When CZ-RWSC2 is used, wireless control becomes possible for all indoor units

- When a separate receiver is set up in a different room, control from that room also becomes possible
- Automatic operation by means of the emergency operation button is possible even when the remote controller has been lost or the batteries have been exhausted

In addition, there are other functions such as temperature setting, operation switching, airflow direction/fan speed setting, etc.



For all indoor
units
CZ-RWSC2

Ventilation independent operation is possible

When commercial ventilation fans or heat-exchange ventilation fans have been installed, they can be operated with this remote control (interlocked operation with the indoor unit or independent ventilation ON/OFF).

Simplified remote controller (CZ-RE2C2)



Dimensions
H 120 x W 70 x D 17 mm

A remote controller with simple functions and basic operation

- Suitable for open rooms or hotels where detailed functions are not required
- ON/OFF, operation mode switching, temperature setting, airflow velocity switching, airflow direction setting, alarm display and remote controller self-diagnosis can be performed
- Batch group control for up to 8 indoor units
- Remote control by main remote controller and sub controller is possible with a simplified remote controller or a wired remote controller (up to two units)

Backlit remote controller [CZ-RELC2]



Dimensions
H 120 x W 70 x D 16 mm

Backlit remote controller with simple and friendly operation

- LCD backlight display (ideal for bedrooms)
- ON/OFF, operation mode switching, temperature setting, airflow velocity switching, airflow direction setting, alarm display and remote controller self-diagnosis can be performed
- Built-in temp sensor
- Batch group control for up to 8 indoor units

System controller (CZ-64ESMC2)



Dimensions
160 x W 160 x D 21 + 69
(embedding dimension mm)

Power supply: AC 220 to 240 V
I/O part: Remote input (effective voltage: DC 24 V): All ON/All OFF Remote output (voltage-free contact): All ON/All OFF (external Power supply within DC 30 V, max 1 A)
Total wiring length : 1 km

- A control mode corresponding to the use condition can be selected from 10 patterns

A : Operation mode: Central control mode or remote control mode can be selected

Central control mode: The system controller is used as centralised control device. (Setting from a remote controller can be prohibited by prohibiting local operation from the system controller.)

Remote control mode: The system controller is used as a remote controller. (Setting from the system controller can be prohibited by prohibiting local operation from another central control unit.)

B : Controlled unit number mode: All mode or zone 1, 2, 3, 4 mode can be selected

All mode: All, zone, or group unit can be selected.

Zone 1, 2, 3, 4 mode: Setting is possible only for the indoor units of zone 1, 2, 3, or 4.

Individual control is possible for max 64 groups, 64 indoor units.

- Control of 64 indoor units divided into 4 zones. (One zone can have up to 16 groups, and one group can have up to 8 units.)
- Control is possible for ON/OFF, operation mode, fan speed, air flow direction (only when used without a remote controller), operation monitoring, alarm monitoring, ventilation, remote controller local operation prohibition, etc.

- Individual All operations are possible also from the remote controller. However, the contents will be changed to the contents of the controller operated last.
- Central 1 The remote controller cannot be used for ON/OFF. (All other operations are possible from the remote controller.)
- Central 3 The remote controller cannot be used for mode change or temperature setting change. (All other operations are possible from the remote controller.)
- Central 4 The remote controller cannot be used for operation mode change. (All other operations are possible from the remote controller.)

| Connection example | | | |
|-------------------------------|-------------|-------------------------------------|------------------------------------|
| | | A Operation Mode | |
| | | Central Control Mode | Remote Control Mode |
| B Controlled unit number mode | All mode | All central control Example 1 | All remote control |
| | Zone 1 mode | Zone 1 central control Example 2 | Zone 1 remote control |
| | Zone 2 mode | Zone 2 central control | Zone 2 remote control Example 3 |
| | Zone 3 mode | Zone 3 central control Example 4 | Zone 3 remote control |
| | Zone 4 mode | Zone 4 central control | Zone 4 remote control Example 5 |


- Joint use with a remote controller, an intelligent controller, a schedule timer, etc. is possible

(The maximum number of connectable system controllers is 10, including other central controllers on the same circuit.)

(In case of joint use with a wireless remote controller, there are limitations for the control mode. Please use only with "Individual" and "Central 1".)

- Control of systems without a remote controller and of main/sub systems (a total of up to 2 units) is possible

Connection example 2 (POWER SUPPLY FROM THE CENTRAL CONTROLLER)



Centralised Control Systems

Schedule timer (CZ-ESWC2)



Dimensions
H 120 x W 120 x D 16 mm

Up to 64 groups (max 64 indoor units) can be controlled divided into 8 timer groups

- Six program operations (Operation/Stop/ Local permission/ Local prohibition) per day can be set in a program for one week
- Only operation or stop, remote controller local permission or remote controller local prohibition, and their respective combinations are possible. (Operation + local permission, stop + local prohibition, only local permission, etc.)
- Local prohibition and the combination of the three items of temperature setting, mode change, and operation/stop can be set at the time of installation.

- A function for pausing the timer in case of national holidays has been added, and timer operation also can be stopped for a long time

- By setting holidays or operation stop within one week, the timer can be paused just for that week.
- All timer settings can be stopped with the timer "ON/OFF effective" button. (Return to timer operation is made by pressing the button again.)


The power supply for the schedule timer is taken from one of the following.

1. Control circuit board (T10) of a nearby indoor unit (power supply wiring length: within 200m from the indoor unit).
2. System controller (power supply wiring length: within 100 m from the indoor unit).

When the power supply for the schedule timer is taken from the control circuit board of the indoor unit, that indoor unit cannot be used with other control devices using the T10 terminal.

As operation mode and temperature settings are not possible with the schedule timer, it must be used together with a remote controller, a system controller, an intelligent controller, etc. Also, as it does not have an address setting function, the control function of a system controller etc. must be used for address setting.

Connection example 1 (POWER SUPPLY FROM THE INDOOR UNIT)



ON/OFF controller (CZ-ANC2)



Dimensions
H 121 x W 122 x D 14 + 52
(embedding dimension mm)

- 16 groups of indoor units can be controlled
- Collective control and individual group (unit) control can also be performed
- Up to 8 ON/OFF controller (4 main, 4 sub) can be installed in one link system
- The operation status can be determined immediately

Note: As operation mode and temperature settings are not possible with the ON/OFF controller, it must be used together with a remote controller, a system controller etc.

Power supply: AC 220 to 240 V
I/O part: Remote input (effective voltage: within DC 24 V): All ON/OFF
Remote output (allowable voltage: within DC 30 V): All ON,
All alarm

Web Interface Systems

Web Interface (CZ-CWEBC2)



(Dimensions: H 248 x W 185
x D 80 mm)

AC 100 to 240 V (50/60Hz),
17 W (separate power supply)

Functions

- Access and operation by Web browser
- Icon display
- Language codes available in English, French, German, Italian, Portuguese, Spanish
- Individual control possible (max. 64 indoor units) ON/OFF operation mode, set temperature, fan speed, Flap set, timer on/off alarm code monitoring, prohibit Remote Control
- Zone control *
- All Units control
- Alarm Log
- Mail Sent Log
- Program Timer set 50 daily timers with 50 actions each day, 50 weekly timers, 50 weekly timers, 1 holiday timer, 5 special day timers, for each tenant
- Prohibit Remote Control set
- IP ADDRESS could be changed via Internet

Note: It is recommended to install a remote controller or a system controller on site to enable local control if the network experiences a problem.

*Power supply



Easy to set to every room by recognisable icon and user-friendly remote control window

If any of the indoor units are selected, the remote control window shown will be displayed for detailed setting modifications.




Easy to manage and monitor each tenant's use *

Each floor or tenant, or otherwise each zone can be displayed and controlled. All unit statuses can also be displayed on one screen.



Programme Timer set
50 daily timers with 50 actions each day, 50 weekly timers, holiday timer, 5 special day timers, for each tenant.

* Web interface system not applicable for load distribution.



Intelligent controller (CZ-256ESMC2)



Touch panel

Dimensions
H 240 x W 280 x D 138 mm
Power supply AC 100 to 240 V (50 Hz), 20 W (separate power supply)
I/O part Remote in put (voltage-free contact): All ON/OFF
Remote output (voltage-free contact): All ON, All alarm
(external power supply within DC 30 V, 0.5 A)
Total wiring length: 1 km for each system
Only for embedding in the panel

- Max 256 indoor units (4 systems x 64 units) can be controlled. In case of three or more systems (more than 129 units), a communication adapter CZ-CFUNC2 must be installed
- Operation is possible as batch, in zone units, in tenant and in group units
- ON/OFF, operation mode setting, temperature setting, for fan speed setting, air flow direction setting (when used without a remote controller), and remote controller local operation prohibition (prohibition 1, 2, 3, 4) can be done
- A system without a remote controller is possible. Joint use with a remote controller or a system controller is also possible
- Use of a schedule timer and holiday setting also can be done
- Proportional distribution of the air conditioning energy is possible. Including csv-file export via CF-card (supplementary accessory)
- NEW function: Pulse signal input from electric/gas consumption meter

In case of joint use with a wireless remote control system, there are limitations for the control mode. Please use only with "Permission" and "Prohibition 1".




Web application

• Limitation contents for prohibited operation

Prohibition means limitation of the operation contents from the remote controller. It is also possible to change the prohibition items.

Limitation contents (Limitations can be user defined)

- | | |
|---------------|--|
| Individual | There is no limitation for the operation of the remote controller. However, the contents will be changed to the contents of the controller operated last. (Last-pressed priority.) |
| Prohibition 1 | The remote controller cannot be used for ON/OFF. (All other operations are possible from the remote controller.) |
| Prohibition 2 | The remote controller cannot be used for ON/OFF, operation mode change and temperature setting. (All other operations are possible from the remote controller.) |
| Prohibition 3 | The remote controller cannot be used for operation mode change and temperature setting. (All other operations are possible from the remote controller.) |
| Prohibition 4 | The remote controller cannot be used for operation mode change. (All other operations are possible from the remote controller.) |



Display sample Max. 4 links can be connected for the indoor/outdoor operation line = Max. 64 indoor units x 4 (256 units)
Max. 30 outdoor units x 4 (120 units)

Communication adaptor (CZ-CFUNC2)



* Required when more than 129 indoor units are connected.

Panasonic total air conditioning management system P-AIMS

P-AIMS Basic software / CZ-CSWKC2

Up to 1024 indoor units can be controlled by one PC

Functions of basic software


- Standard remote control for all indoor units
- Many timer schedule programs can be set on the calendar
- Detailed information display for alarms
- CSV file output with alarm history, operating status
- Automatic data backup to HDD



With 4 upgrade packages the basic software can be upgraded to suit individual requirements




CZ-CFUNC2



P-AIMS is ideal for large areas/buildings such as shopping centres, universities and office buildings.

Up to eight Communication Adaptors (C/A) can be connected to a P-AIMS to enable control of 1024 indoor units with one "P-AIMS" PC.



P-AIMS optional software CZ-CSWAC2 for Load distribution

Load distribution calculation for each tenant

- Air-conditioner load distribution ratio is calculated for each unit (tenant) with used energy consumption data (m3, kWh)
- Calculated data is stored with CSV type file
- Data of last 365 days is stored



P-AIMS optional software CZ-CSWWC2 for Web application

Web access & control from remote station


- Accessing P-AIMS software from remote PC
- You can monitor/operate FSV systems by using Web browser (Internet Explorer)



P-AIMS optional software CZ-CSWGC2 for Object layout display

Whole system can be controlled visually


- Operating status monitor is available on the layout display
- Object's layout and indoor unit's location can be checked at once
- Each unit can be controlled by virtual remote controller on the display
- Max 4 layout screens are shown at once



P-AIMS optional software CZ-CSWBC2 for BACnet software interface

Connectable to BMS system

- Can communicate with other equipment by BACnet protocol.
- FSV systems can be controlled by both BMS and P-AIMS.
- Max 255 indoor units can be connected to 1 PC (that has P-AIMS basic & BACnet software).




T10 Terminal for External Control (Digital Connection)

Connecting an indoor unit to an external device is easy.
The T10 Terminal featured in the electronic circuit board of all indoor units enables digital connection to external devices.




1. T10 Terminal Specification (T10:CN061 at indoor unit PCB)

- Control items: 1. Start/stop input
2. Remote controller prohibit input
3. Start signal output
4. Alarm signal output



NOTE: The wire length from indoor unit to the Relay must be within 2.0m
Pulse signal changeable to static with JP cutting. (Refer to JP001)

• Example of wiring



Condition

- 1-2 (Pulse input): Unit ON/OFF condition switching with a pulse signal.
(1 pulse signal: shortage status more than 300msec. or more)
- 2-3 (Static input): Open/ Operation with Remote is permitted. (Normal condition) Close/ Remote controller is prohibited.
- 3-4 (Static output): 12V output during the unit ON. / No output at OFF
- 4-5 (Static output): 12V output when some errors occur / No output at normal


2. Usage Example

Forced OFF control

• Condition

1-2 (Static input): Close/ Operation with Remote is permitted. (Normal condition) Open/ Unit is forcibly OFF and Remote controller operation is prohibited.

• Example of wiring




NOTE: The wire length from indoor unit to the Relay must be within 2.0m

Operation ON/OFF signal output

• Condition

4-5 (Static output): 12V output during the unit ON / No output at OFF

• Example of wiring



NOTE: The wire length from indoor unit to the Relay must be within 2.0m
Pulse signal changeable to static with JP cutting. (Refer to JP001)

Serial Interface for 3rd Party External Controller

Example of 3rd party BMS connection with CZ-CFUNC2
(For details please consult an authorised dealer)

| Functions via communication adaptor [CZ-CFunc2] | |
|---|--------------------------|
| A/C unit settings | Unit ON/OFF |
| | Mode-change |
| | Room temperature setting |
| | Fan speed setting |
| | Flap setting |
| | Central control setting |
| | Filter-sign clear |
| | Alarm reset |
| A/C unit status | Unit ON/OFF status |
| | Operation mode |
| | Setting temperature |
| | Fan speed status |
| | Flap status |
| | Central control setting |
| | Filter-sign situation |
| | Correct/incorrect status |
| | Alarm code |

Communication adaptor
(CZ-CFUNC2)



Up to 128 indoor units can be connected to one Communication Adaptor.

Flexible Design Options

Remote temperature sensor (CZ-CSRC2)



Dimensions
H 120 x W 70 x D 16 mm

- This is a remote sensor which can be used with indoor units to detect the room temperature when no remote controller sensor or body sensor is used. (Connection to a system without a remote controller is possible).
- For joint use with a remote control switch, use the remote control switch as main remote controller.

Interfaces for External Control (Digital Connection)


Seri-Para I/O unit for outdoor unit (CZ-CAPDC2)



| | |
|---------------|--|
| Dimensions | H 80 x W 290 x D 260 mm |
| Power supply | Single phase 110-120/220-240 V AC (50/60 Hz), 18 W |
| Input | Batch operation/Batch stop (non-voltage contact/DC 24 V, pulse signal). Cooling/Heating (non-voltage contact/static signal). Demand 1/2 (non-voltage contact/static signal) (Local stop by switching) |
| Output | Operation output (non-voltage contact). Alarm output (non-voltage contact) |
| Wiring length | Indoor/Outdoor operation lines: Total length 1 km. Digital signal: 100 m or shorter |

- This unit can control up to 4 outdoor units
- From the centre control device, mode changing and batch operation/batch stop are possible
- Required for demand control

System example




Seri-Para I/O unit for each indoor unit (CZ-CAPBC2)



- Control and status monitoring is possible for individual indoor unit (1 group)
- In addition to operation and stop, there is a digital input function for air speed and operation mode
- Temperature setting and measuring of the indoor suction temperature can be performed from central monitoring
- The analog input for temperature setting is 0 to 10 V, or 0 to 140 Ohm
- Power is supplied from the T10 terminal of the indoor units.
- Separate power supply also is possible (in case of suction temperature measuring)

System example




Interface adaptor (CZ-CAPC2)



- Control and status monitoring is possible for individual indoor unit (or any external electrical device up to 250 V AC, 10 A) by contact signal

System example




LonWorks Interface (CZ-CLNC2)



- This interface is a communications converter for connecting LonWorks to the control network of FSV.
- From the host connected to LonWorks, basic settings and status monitoring is possible for up to 16 groups of A/C units

System example




Functions


| | | |
|---|---|---------------------------------------|
| Functions | | |
| A/C unit settings from the LonWorks communicator | Settings for each group of indoor units | Start/stop |
| | | Temp. setting |
| | | Operation mode |
| | | Option 1 settings(*) |
| | Option 2 settings(*) | |
| | Settings for all units | Emergency stop |
| A/C unit status notifications made to the LonWorks communicator | | Start/stop |
| | | Temp setting |
| | | Operation mode |
| | | Option 1 settings(*) |
| | | Option 2 settings(*) |
| | | Alarm status |
| | | Indoor units with active alarms |
| | | Room temp. |
| Configuration properties | | A/C unit status |
| | | Transmission intervals settings |
| | | Minimum time secured for transmission |

Remote Controller External Dimensions


TIMER REMOTE
CONTROLLER
(CZ-RTC2)




WIRELESS REMOTE
CONTROLLER
(CZ-RWSU2, CZ-RWSC2)




SEPARATE RECEIVER FOR
WIRELESS REMOTE CONTROLLER
(CZ-RWSC2)




SIMPLIFIED REMOTE
CONTROLLER
(CZ-RE2C2)




SYSTEM CONTROLLER
(CZ-64ESMC2)




BACKLIT REMOTE
CONTROLLER
(CZ-RELC2)
REMOTE SENSOR
(CZ-CSRC2)




COMMUNICATION ADAPTOR
(CZ-CFUNC2)




INTELLIGENT CONTROLLER
(CZ-256ESMC2)




ON/OFF CONTROLLER
(CZ-ANC2)




SERI-PARA I/O UNIT FOR EACH INDOOR UNIT
(CZ-CAPBC2)



LONWORKS INTERFACE
(CZ-CLNC2)



SERI-PARA I/O UNIT FOR OUTDOOR UNIT
(CZ-CAPDC2)



EVERY BUILDING MATTERS

'eco ideas' Declaration



'eco ideas' for Lifestyles

We will promote lifestyles with virtually zero CO₂ emissions all throughout the world

'eco ideas' for Business-styles

We will create and pursue a business-style which makes the best use of resources and energy



Panasonic

Panasonic Australia Pty. Limited.

ACN 001 592 187 ABN 83 001 592 187

www.panasonic.com.au